

ORDER

(Request Approval to Advertise for Bids for Two (2 each) Single Axle Dump Chassis with Mounted Dump Body for Sewer Lines)

WHEREAS, the City of Laurel requests approval to advertise for bids for two (2) new Single Axle Dump Chassis with Mounted Dump Body.

WHEREAS, this purchase will be made using the reverse auction bid.

THEREFORE IT IS ORDERED by the Mayor and the Laurel City Council, that a “Single Axle Dump Chassis with Mounted Dump Body” be advertised for bid. The Dump Trucks are needed for the Sewer Lines Department and funds for lease purchase of two each Dump Trucks are budgeted in 400-726-866.0.

(NOTICE TO BIDDERS)

(COPY OF SPECS)

SO ORDERED this the 4th day of December, A.D., 2018.

Motion was made by Councilperson Capers, and seconded by Councilperson T. Comegys that the above and foregoing Order be adopted.

YEAS: Capers, Wheat, Thaxton, Carmichael, S. Comegys, T. Comegys, Page

NAYS: None

ABSTAINING: None

ABSENT: None

The President thereupon declared the motion carried and the order adopted, this the 4th day of December 4th, A.D., 2018.

PRESIDENT of the COUNCIL

Attested and submitted to the Mayor by the Clerk of the Council on
_____.

CLERK of the COUNCIL

APPROVED () DATE _____

VETOED () DATE _____

MAYOR

ATTEST:

CITY CLERK

Min. of 12/04/18 Bk. No. 101 Pg. _____; AGENDA ITEM NO. 4A

NOTICE TO BIDDERS

Notice is hereby given that BIDS will be received by the City of Laurel for the purchase of a two (2) new

“TWO (2) SINGLE AXLE DUMP CHASSIS WITH MOUNTED DUMP BODY”

Specifications for the Single Axle Dump Chassis with Mounted Dump Body may be obtained at the City Clerk's office in City Hall, 401 N. Fifth Ave., Laurel, Mississippi, and on our Reverse Auction site at: www.centralbidding.com. Specification responses are to be filed with the City Clerk, City Hall, Laurel, Mississippi, or on www.centralbidding.com prior to 5:00 P.M. local time, Wednesday, December 26, 2018, at which time proposals will be opened and qualified for the reverse auction. Approved bidders will then receive email notification of eligibility. For any questions relating to the electronic bidding process, please call Central Bidding at 225-810-4814.

DO NOT INCLUDE PRICING INFORMATION WITH YOUR SPECIFICATION RESPONSE. BIDS WILL ONLY BE TAKEN ONLINE AT THE APPOINTED TIME AND DATE.

Registration with Central Bidding and acceptance of the Central Bidding Agreement is not optional and is required in order to participate in this bidding event. No exceptions will be made. Bids will be received by an Electronic Sealed Bidding Process administered by Central Bidding at the CITY OF LAUREL City Clerk's office, Laurel, Mississippi, on Friday, 12/28/2018 at 10:00 AM CST at which time bidding will begin and run until suppliers have completed entering all bids. The City of Laurel reserves the right to reject any and/or all bids.

The city reserves the right to utilize “anti-sniping” for reverse auctions. Anti-sniping is a tool that automatically extends the bid time for a reverse auction by five (5) minutes if a vendor places a bid in the final five (5) minutes of the reverse auction. The anti-sniping effect will auto extend the reverse auction bid time any time a bid is placed in the last five (5) minutes of the reverse auction and can auto extend the reverse auction multiple times until the bidding on the reverse auction ends.

This the 4th Day of December, 2018.

Mary Ann Hess, City Clerk

Please publish on December 11 and December 18, 2018.

BID SPECIFICATIONS
Single Axle Dump Chassis
2019 YEAR MODEL

	YES	NO	OFFERED
WHEEL BASE / FRAME			
WHEELBASE 180" or to accommodate body builder 98 CA	<input type="checkbox"/>	<input type="checkbox"/>	<input type="text"/>
FRAME: 1/2 X 3.64 X 11 7/8 3.2 minimum RBM frame strength	<input type="checkbox"/>	<input type="checkbox"/>	<input type="text"/>
BUMPER: CHROME STEEL BUMPER W/ TOW HOOKS	<input type="checkbox"/>	<input type="checkbox"/>	<input type="text"/>
Rear Tow Hooks	<input type="checkbox"/>	<input type="checkbox"/>	<input type="text"/>
Trailer Towing Package	<input type="checkbox"/>	<input type="checkbox"/>	<input type="text"/>
ENGINE			
MIN 350 HP, 1150 LB/FT TORQUE	<input type="checkbox"/>	<input type="checkbox"/>	<input type="text"/>
EXHAUST: SINGLE RH MOUNTED WITH Horizontal TAILPIPE	<input type="checkbox"/>	<input type="checkbox"/>	<input type="text"/>
RH OUTBOARD UNDER STEP MOUNTED Vertical AFTER TREATMENT SYSTEM	<input type="checkbox"/>	<input type="checkbox"/>	<input type="text"/>
RADIATOR: MINIMUM 1300 SQUARE INCH	<input type="checkbox"/>	<input type="checkbox"/>	<input type="text"/>
ALTERNATOR: 12 VOLT 160 AMP	<input type="checkbox"/>	<input type="checkbox"/>	<input type="text"/>
BATTERIES: 3 MINIMUM 2190 CCA	<input type="checkbox"/>	<input type="checkbox"/>	<input type="text"/>
18.7 Air Compressor / Positive Load Disconnect in Cab	<input type="checkbox"/>	<input type="checkbox"/>	<input type="text"/>
TRANSMISSION / TIRES			

TRANSMISSION: Allison 3000 RDS Automatic
with PTO Provision

☐☐

Block Heater

☐☐

11R22.5 Front Tires - HWY
Steel Hub Pilot wheels

☐☐

11R22.5 Rear Tires - Closed Shoulder
Steel Hub Pilot Wheels

☐☐

FRONT AXLE

12,000 Pound

☐☐

SPRINGS: MINIMUM 12,000 LB TAPER LEAF

☐☐

FRONT SHOCK absorbers

☐☐

BRAKES: FRONT 16.5 x 5 Q+ HD

☐☐

Synthetic Axle Lube

☐☐

Air Dryer With Heater

☐☐

Automatic Slack Adjusters

☐☐

REAR AXLES

Minimum 23,000 LB

☐☐

SUSPENSION: Minimum 23,000 LB

☐☐

REAR BRAKES: 16.5 X 7 P CAM Brakes

☐☐

Automatic Slack Adjusters

☐☐

Synthetic Axle Lube

☐☐

Driver Traction Control Differential Lock

☐☐

CAB INTERIOR

RADIO: AM/FM

☐☐

Premium Interior - Wood grain Dash/Chrome bezels

☐☐

Double cup holder with cell phone holder

☐☐

2-1/2 LB. Fire Extinguisher Mounted Next to Driver Seat

☐☐

Automatic Reset Circuit Breakers in Dash

☐☐

Interior Armrest - Passenger/Driver

☐☐

HEATER & AIR CONDITIONER

☐☐

Daytime running Lights

☐☐

SEATS: DRIVER HIGH BACK AIR SUSPENSION

☐☐

Passenger Seat non-air ride

☐☐

SEAT COVERS: VINYL

☐☐

GAUGES WITH BRIGHT BEZELS

Engine Brake

☐☐

PRIMARY AND SECONDARY AIR PRESSURE

☐☐

FUEL GAUGE

☐☐

ENGINE COOLANT TEMPERATURE

☐☐

ENGINE OIL PRESSURE

☐☐

Fuel/Water Seperator

☐☐

VOLT METER

☐☐

Speedometer / Odometer / Hour Meter

☐☐

Backup Alarm

CAB EXTERIOR

All STEEL CAB SHELL - 5 year warranty

☐☐

Air Cab Mounts

☐☐

TINTED TWO PIECE WINDSHIELD

☐☐

DUAL STAINLESS STEEL MIRRORS - Heated w/Lights

☐☐

SPOT MIRRORS: 8" CONVEX MIRRORS LH & RH
MOUNTED BELOW PRIMARY MIRRORS

☐☐

Single Electric Horn

☐☐

FUEL TANKS

LH 80 GAL ALUMINUM FUEL TANK

☐☐

DEF TANK: 13 GAL LEFT SIDE MOUNT

☐☐

PAINT

CAB: WHITE BASE/CLEAR

☐☐

CHASSIS: BLACK

☐☐

WARRANTY/Service

1 YEAR / 100,000 MILE BASE WARRANTY ON CHASSIS

☐☐

ENGINE:

2 YEAR / Unlimited MILES PARTS & LABOR WARRANTY

☐☐

EXTENDED WARRANTIES:

ROADSIDE ASSISTANCE & TOWING:

5 Year Coverage, Included in Price

☐☐

5 year truck chassis coverage (Tc4 Equivalent)	<input type="checkbox"/>	<input type="checkbox"/>	_____
5 Year Premium Engine Warranty (HD1 Equivalent)	<input type="checkbox"/>	<input type="checkbox"/>	_____
5 Year Aftertreatment Warranty	<input type="checkbox"/>	<input type="checkbox"/>	_____
5 Year Transmission Warranty	<input type="checkbox"/>	<input type="checkbox"/>	_____
5 Year Axle Warranty	<input type="checkbox"/>	<input type="checkbox"/>	_____
5 Year Electrical Warranty	<input type="checkbox"/>	<input type="checkbox"/>	_____
Must provide service location within 40 miles that handles towing/parts/warranty/service	<input type="checkbox"/>	<input type="checkbox"/>	_____ _____
State Delivery time as that will be a factor in determining best bid	<input type="checkbox"/>	<input type="checkbox"/>	_____ _____

DUMP BODY

Body Length - 10 feet	<input type="checkbox"/>	<input type="checkbox"/>	_____
Inside Width - 7 feet 10 Inches	<input type="checkbox"/>	<input type="checkbox"/>	_____
Side Height - 32 Inches	<input type="checkbox"/>	<input type="checkbox"/>	_____
Tailgate Height - 38 Inches	<input type="checkbox"/>	<input type="checkbox"/>	_____
Front Height - 38 Inches	<input type="checkbox"/>	<input type="checkbox"/>	_____
Body Sides, Front and Tailgate - 10 ASTM-A1011-A45 Hi-Tensile Steel	<input type="checkbox"/>	<input type="checkbox"/>	_____ _____
Body Floor - 3/16 Inch ASTM-A1011-A45 Hi-Tensile Steel	<input type="checkbox"/>	<input type="checkbox"/>	_____
Top Rail - 4 Inch x 4 Inch x 1/8 Inch tubing	<input type="checkbox"/>	<input type="checkbox"/>	_____
Side Braces - 6 Inch Boxed	<input type="checkbox"/>	<input type="checkbox"/>	_____
Water Level Capacity - 7 Yard	<input type="checkbox"/>	<input type="checkbox"/>	_____

Front & Tailgate Capacity - 8 Yard

☐☐

Longitudinals - 5 inch Structural Channel

☐☐

Crossmembers - 3 inch Structural Channel on 12 Inch Centers

☐☐

Boards - 2 Inch x 6 Inch Tubing (Bolt In)

☐☐

Tailgate - 3 Panel, No Slope, Air Latch, Double-Acting, 5/16 Inch Chains

☐☐

Cab Shield - 1/2 W/4 Inch Integral Wind Deflector

☐☐

Hoist - NTEA Rated Class 70 Front Telescopic

☐☐

Hyd Pump - 22 GPM @ 1400 RPM To Be Integrally Mounted to PTO Air Shift w/Feathering Valve

☐☐

Controls - Console Type Elec Hyd PTO/Air Pump

☐☐

Apron - 8", Weld-On

☐☐

PTO - For Allison Automatic Transmission

☐☐

Tow Package - 20T Pintle Hook W/D-Rings, Plumb Air/Elec Lines To Plate

☐☐

Lights - LED To Meet FMVSS 108

☐☐

Warning Lights - (2) 6 Inch Oval LED Flashing In Cab Shield
(1) 6 Inch Oval LED Flashing in Each Rear Post
In-Cab Switch For Warning Lights

☐☐

Full Depth Rear Corner Post And Skirt

☐☐

All Welds To Be Continuous

☐☐

Body Prop

☐☐

Body Raised Indicator Light

☐☐

Backup Alarm	<input type="text"/>	<input type="text"/>	<hr/>
Primed And Finish Painted Gloss Black Urethane Enamel	<input type="text"/>	<input type="text"/>	<hr/>
Recommended CA-84 Inch	<input type="text"/>	<input type="text"/>	<hr/>

Please bid these at individual prices but we will be purchasing two.